



PS 44A/F  
Power Amplifier

Features:

- 4-Channel Power Amplifier
- Large Output Power, Stable and Reliable Performances
- PS44F has a built-in DSP and supports FIR phase correction function.



Technical Specifications:

In/Outputs	Output Power	4 Channel Mode	4Ω	4×750W
			8Ω	4×400W
		3 Channel Mode	1×1400W @ 8Ω BTL + 2×750W @ 4Ω	
			1×1400W @ 8Ω BTL + 2×400W @ 8Ω	
		2 Channel Mode	Bridged 8Ω	2×1400W
	Input Connectors		XLR Female	
	Link Connectors		XLR Male	
	Output Connectors		Speakon Connectors	
	Sensitivity (dB)		41dB 32dB 26dB	
Power Supply		AC 100-240V ~ 50-60Hz		
Nominal Parameters	Input Impedance	Balanced	20KΩ	
		Unbalanced	10KΩ	
	Frequency Response		10Hz-30kHz (±1dB) @1W, 8Ω	
	THD		<0.08%	
	S/N Ratio (dB)		>115dB	
	Damping Factor		>500 @1kHz	
	Weight		7kg	
	Dimensions (WxDxH)		483×420×88mm	
Protect	Short-circuit Protect, Overload Protect, Overheat Protect			