



↘ **TANG 32**

Power Amplifier

Features:

- ↘ 2-Channel Power Amplifier
- ↘ High Output and Reliability



Technical Specifications:

|                |                                                |                                  |
|----------------|------------------------------------------------|----------------------------------|
| Input/Output   | Output Power 16Ω                               | 2×600W                           |
|                | 8Ω                                             | 2×1100W                          |
|                | 4Ω                                             | 2×1600W                          |
|                | Bridge 16Ω                                     | 1×3200W                          |
|                | Input Connector                                | XLR Female                       |
|                | Link Connector                                 | XLR Male                         |
|                | Output Connector                               | Speakon Connectors               |
|                | Sensitivity Select(dB)                         | 41dB 32dB 26dB                   |
|                | Power Supply                                   | AC 100-240V ~ 50-60Hz            |
| Specifications | Input Impedance Balanced                       | 20KΩ                             |
|                | Unbalanced                                     | 10KΩ                             |
|                | Frequency Response                             | 10Hz-25kHz(-3dB)@1W,4Ω           |
|                | THD                                            | < 0.05%                          |
|                | Signal/ noise Ratio (dB)                       | >115 dBA (20Hz-20kHz, A Weighted |
|                | Conversion Rate                                | 50v/μs                           |
|                | Damping Facotr                                 | >1000 @ 100Hz                    |
|                | Weight                                         | 7kg                              |
| Protect        | Dimensions (WxDxH)                             | 483mm×420mm×88mm                 |
|                | Short-circuit, Over-load, Over-heat Protection |                                  |