



📌 DAD-10

Line Array Speaker

Features:

- 📌 Achieving high sound quality for the transmission of very high SPL vocal sound and full-range music even in reverberant spaces.
- 📌 Compact dimensions; High power handling capacity.
- 📌 3-way line array speaker.



Technical Specifications:

Technical Parameters	DAD-10
Components	HF: 8×1" throat 1.4" voice coil Neodymium HF driver
	MF: 4×5" 38mm voice coil Neodymium MF driver
	LF: 2x 10" 76mm voice coil Neodymium LF driver
Recommended Amplifier (traditional line array connection)	HF: 400W/8Ω
	MF: 800W/8Ω
	LF: 1600W/4Ω
Nominal Impedance	HF: 8Ω
	MF: 8Ω
	LF: 8Ω
Frequency Response	70Hz-20KHz±3dB
Coverage	Hor: 90° (symmetric)
	Ver: 0° -16° (depending on the number and the curvature of the line source) , 1° increment
Sensitivity (1W/1M)	HF:115dB
	MF: 105dB
	LF: 105dB
Maximum SPL (1M)	* 144dB
Connectors (traditional line array connection)	2×Neutrik NL-8; HF:±4、MF: ±3、LF:±1, ±2
Installation manner	Flying or ground stacking (ground-stack frame needed, or stacking on the subwoofer)
Dimension (H×W×D)	294mm× 944mm×400mm
Weight	44Kg