



📌 TANG 10000.4

Power Amplifier

Features:

- 📌 4-Channel Power Amplifier
- 📌 High Output and Reliability
- 📌 Very high power output/dimension ratio
- 📌 Excellent sound quality



Technical Specifications:

Input/Output	Output Power	Stereo	8Ω	4×1600W
			4Ω	4×2650W
		Bridge	16Ω	2×3200W
			8Ω	2×5300W
			4Ω	2×7000W
	Input Connector			XLR
	Output Connector			4 Neutrik NL4
	Sensitivity Select(dB)			0.775V/1V/1.4V/2V
Power Supply			AC 110/220V ~ 50-60Hz	
Specifications	Input Impedance	Balanced	10KΩ	
		Unbalanced	20KΩ	
	Frequency Response			10Hz-20kHz(±0.35dB)
	THD+Noise			≤ 0.5%@8Ω1kHz
	Signal/Noise Ratio(dB)			>99 dBA
	Conversion Rate			>30v/μs
	Damping Factor			>3000 (8Ω) @20Hz- 100Hz
	Voltage gain			43.3dB (0,775V:113V)
	Weight			8.5kg
	Dimensions(W×D×H)			483mm×420mm×45mm
Protect	Short-circuit, Over-load, Over-heat Protection			