



📌 TANG 30000.4

Power Amplifier

Features:

- 📌 4-Channel Power Amplifier
- 📌 High Output and Reliability
- 📌 Very high power output/dimension ratio
- 📌 Excellent sound quality



Technical Specifications:

Input/Output	Output Power	Stereo	8Ω	4×3200W
			4Ω	4×5200W
			2Ω	4×7300W
		Bridge	16Ω	2×6400W
			8Ω	2×11000W
			4Ω	2×13000W
	Input Connector			XLR
	Output Connector			4 Neutrik NL4
	Sensitivity Select(dB)			32dB/35dB/38dB/41dB
	Power Supply			PFC100-240V ~ 50-60Hz
Specifications	Input Impedance	Balanced	10KΩ	
		Unbalanced	20KΩ	
	Frequency Response			10Hz-20kHz(±0.35dB)
	THD+Noise			≤ 0.5%@8Ω1kHz
	Signal/Noise Ratio(dB)			>99 dBA
	Conversion Rate			>30v/μs
	Damping Factor			>3000 (8Ω) @20Hz- 100Hz
	Voltage gain			46.3dB (32dB:160V)
	Weight			12.3kg
	Dimensions(W×D×H)			483mm×486mm×45mm
Protect	Short-circuit, Over-load, Over-heat Protection			