



## 📌 DAD12M

Line Array Speaker

### Features:

- 🎯 Very high SPL with a longer throw HF coverage.
- 🎯 High power handling capacity.
- 🎯 3-way line array speaker.



### Technical Specifications:

Technical Parameters	DAD12M
Components	HF: 10×1" throat 1.4" voice coil Neodymium HF driver MF: 4×6.5" 38mm voice coil Neodymium MF driver LF: 2×12" 100mm voice coil LF driver
Continuous Program Power (single cabinet)	HF: 700W/6.4Ω MF: 1600W/8Ω LF1: 2000W/8Ω, LF2: 2000W/8Ω
Nominal Impedance	HF: 6.4Ω MF: 8Ω LF1: 8Ω, LF2: 8Ω
Frequency Response	HF: 1500Hz-20KHz MF: 200Hz-1500Hz LF: 45Hz-200Hz
Coverage	Hor: 50°, 70°, 90°, 110°, 130° optional (symmetric) Ver: 0° -10° in 1° step (0.5° first step) Dependent upon the number of elements and the line source curvature
Sensitivity (1W/1M)	HF50°: 115dB, HF70°: 114 dB, HF90°: 114dB, HF110°: 113dB, HF130°: 113dB MF: 101dB LF1: 95dB, LF2: 95dB
Maximum SPL (1M)	* 146dB
Connectors	YYH-8PA, YYH-8PB; HF: G+, H-, MF: E+, F-, LF1: A+, B-, LF2: C+, D-
Installation manner	Flying or ground stacking (ground-stack frame needed, or stacking on the subwoofer)
Dimension (W×H×D)	1080mm x 492mm x 380mm
Weight	80Kg