



⏏ SIC 15000.4

Power Amplifier

Features:

- 🔍 4-Channel Power Amplifier
- 🔍 High Output and Reliability
- 🔍 Very high power output/dimension ratio
- 🔍 Excellent sound quality



Specifications:

Input/Output	Output Power	Stereo	8Ω	4 x 1500W	
			4Ω	4 x 2500W	
			2Ω	4 x 3700W	
		Bridge	16Ω	2 x 3000W	
			8Ω	2 x 4950W	
			4Ω	2 x 6600W	
	Input Connector			XLR	
Output Connector			4 Neutrik NL4		
Sensitivity Select(dB)			0.775V/1V/1.4V/2V		
Power Supply			AC 110/220V ~ 50-60Hz		
Specifications	Input Impedance	balanced	10KΩ		
		Unbalanced	20KΩ		
	Frequency Response			10Hz-20kHz(±0.35dB)	
	THD+Noise			≤ 0.5%@8Ω1kHz	
	Signal/Noise Ratio(dB)			> 102 dB	
	Crosstalk (1kHz)			> 70dB	
	Conversion Rate			> 30v/μs	
	Damping Factor			> 3000 (8Ω) @20Hz-100Hz	
	Voltage gain			43dB (0,775V:110V)	
	Operating Voltage			PFC 90-270V	
	Fuse			F-15A*2	
	Power consumption(Idle)			< 130W	
	Power consumption(Max)			< 5800W	
	Circuit			Class D	
	Dimensions (L×W×D)			483mm×415mm×45mm (1U)	
Package (L×W×D)			610mm×500mm×100mm		
Net Weight			11.2kg		
Gross Weight			14.2kg		
Protect	short-circuit, DC,overload, overheat,ultrasonic, RF, voltage peak limit				