



KT4MH+KT15B+KT18S

High end KTV system speakers



Features:

- Horizontal 80° - 120° (gradient) wide coverage.
- MF & HF coaxial speakers and point source make the sound more accurate.
- Supersize horn achieves better sound control.

Technical Specifications:

Technical Parameters	KT4MH	KT15B	KT18S
Components	65mm (HF) voice coil + 100mm (MF) voice coil neodymium MF & HF coaxial speakers (built-in passive crossover)	15" neodymium driver *1 (LF voice coil: 88mm)	18" neodymium driver *1 (LF voice coil: 100mm)
Recommended Amplifier	380W	1400W	2000W
Nominal Impedance	8Ω	8Ω	8Ω
Frequency Response	300Hz-18KHz	50Hz-1000Hz	30Hz-200Hz
Coverage	Hor: 80-120° (gradient) Ver: 50°	/	/
Sensitivity (1W/1M)	112dB	99dB	101dB
Max. SPL (1M) *	138dB	133dB	134dB
Connectors	2×Neutrik NL-4; ±1	2×Neutrik NL-4; ±1	2×Neutrik NL-4; ±1
Installation manner	Flying or ground stacking (4×M8 nuts on both sides of the cabinet)	Flying or ground stacking (4×M8 nuts on both sides of the cabinet)	Flying or ground stacking (4×M8 nuts on both sides of the cabinet)
Dimension (W×H×D)	561mm×561mm×550mm (Height not including the 10mm high machine feet.)	561mm×455mm×550mm (Height not including the 10mm high machine feet.)	561mm×561mm×756mm (Height not including the 10mm high machine feet.)
Weight	27Kg	26Kg	42Kg